

TASKI swingo 1250 B

TASKI swingo 1250B brings you:

- Unbeatable Cleaning Performance
- Increased Productivity and Manoeuvrability
- Excellent Ergonomics
- Simplicity and easy Maintenance



Performance

The patented brush design follows the floor profile and deliversnearly even presure allocation along the full working width. This results in excellent soil removal. The U-shaped squeegee allows excellent water pick-up along the full working width. Special squeegee blades and a direct suction design allow pick-up of small debris (e.g. cigarette butts) without clogging.

Productivity and Manoeuvrability

Increased battery capaacity coupled with a larger tank and the patented CSD system radically increases productivity. The dual-axle system ensures easy handling and allows excellent manoeuvrability in confined areas.

Ergonomics

The ergononomic handle suits all operators. All functions of the machine can be operated from the working position.

Battery powered automatic scrubber drier for floor cleaning

The dashboard is self explanatory with minimum training needed and displays all required information.

Maintenance

Colour coded maintenance points increase efficiency and reduce the need for training. Fewer parts to maintain and easy accessibility make the machine extremely service friendly.

Technical Data	
Theoretical perfomance	2475 m²/h
Working width	55 cm
Squeegee width	75 cm
Solution tank (nomina)l	52 I
Recovery tank (nominal)	50 I
Normal consumption	1000 W
Rated voltage	24 V
Battery capacity	100 - 140 Ah/C5
Battery automony (nominal)	3.5 h
Machine weight ready for use	240 kg
Dimensions (L x W x H)	1332x490x1153 mm
Turning circle	1.33 m
Brush system	2 x 28 cm
Brush pressure	46 kg
Working speed	4.5 km/h
Cable length of integrated battery charger	2.5 m
Noise level	58 dB(A)
Splash water protection	IPX3
Electrical protection class	-



TASKI swingo 1250 B is available in the following versions

Model	Power	Power BMS	Power EBU	Power BMS
Battery Management System (BMS)		Х		Х
Wheel Drive (WD+CSD)	Х	Х	Х	Х
Electric Brush Unit (EBU)			Х	Х

Accessories / Additional Parts

-	-
Acces	sories

Pad drive harpoon grip 28 cm	
Scrubbing brush standard 28 cm	
Scrubbing brush washed concrete 28 cm	
Scrubbing brush abrasive 28 cm	
Filling hose with universal water coupling	
Additional Parts	
Polyurethane traction wheel, brown	
Set of 2 polyurethene traction wheels green (supergrip)	
Polyurethane castor wheel 100mm	
External hour counter	

Description of Features

BMS: Battery Management System: The battery charger which is integrated in the machine, prevents deep discharging of the battery and monitors the charging processs.

WD: Wheel Drive: The variable working speed (up to 4.5km/h) and reverse speed (up to 2.5km/h) guarantees ergonomic and effortless working and increases the performance compared to non-wheel drive models.

CSD: Cleaning Solution Dosing: With the patented CSD system, exactly the right amount of cleaning solution is dosed onto the floor depending on how fast the machine is going. The slower you go (e.g. around corners) the less is dosed. The result is no puddles around corners, a 30-50% saving in cleaning solution and significantly increased productivity of the machine.

EBU: Electrical Brush Unit: The brush unit can be lifted and lowered at the touch of a button. This allows fast and effortless brush changing - even for inexperienced users.



JohnsonDiversey Eschlikonerstrasse CH-9542 Muenchwilen Switzerland Ph. +41-71-969 2727 Fax. +41-71-969 2253 www.johnsondiversey.com

