



## TASKI swingo 1255 B

#### TASKI swingo 1255B brings you:

- The ideal size for best performance
- Excellent cleaning and drying results
- Simple use and easy maintenance
- Durability and robustness



#### Ideal size for beste performance

The patented CSD - system ensures always the right amount of cleaning solution on the floor and leads to significant water savings. This, in combination with the 60 L tank volume, increase productivity and cut the number of time consuming tank filling stops during the cleaning operation. The dual-axle system ensures easy handling and allows comfortable use of the machine.

#### Excellent cleaning and drying results

The patented brush design follows the floor profile and delivers nearly even pressure allocation along the full working width. The 2 brushes with offset to side allow perfect cleaning along walls and under racks. This results in excellent soil removal and floor apprearance. The patented V-shaped squeegee allows perfect water pick-up on all floor types, even on structured and grouted/tiled floors. Special squeegee blades and a direct suction line allow pick-up of small debris (e.g. cigarette butts) without clogging. Due to the proven 3-wheel-concept, adjustments of the squeegee are not necessary anymore.

# Battery powered automatic scrubber drier for floor cleaning

#### Simple use and easy maintenance

All components which need frequent maintenance are colour coded in yellow and can be removed easily without tools. The dashboard is self-explanatory with minimum training needed and displays all required information. Fewer parts to maintain and easy accessibility make the machine extremely service friendly.

#### **Durability and robustness**

The use of high tech material and long life components enhance machine's uptime while reducing service and repair costs to a minimum.

Technical Data	
Theoretical perfomance	2475 m²/h
Working width	55 cm
Squeegee width	80 cm
Solution tank (nomina)I	60 I
Recovery tank (nominal)	60 I
Nominal consumption	1000 W
Rated voltage	24 V
Battery capacity	100 - 140 Ah/C5
Battery automony (nominal)	up to 3 h
Machine weight ready for use	260 kg
Dimensions (L x W x H)	1420x580x1170 mm
Turning circle	1.33 m
Brush system	2 x 28 cm
Brush pressure	48 kg
Cleaning speed	4.5 km/h
Cable length of integrated battery charger	3 m
Sound level	58 dB(A)
Protection class (with BMS / without BMS)	II / III
Approvals	CE/CB Test cert./ ÖVE/cETL



## TASKI swingo 1255 B is available in the following versions

Model	Power	Power BMS	Power EBU	Power BMS
Wheel Drive (WD+CSD)	X	X	X	X
Battery Management System (BMS)		Х		X
Electric Brush Unit (EBU)			Х	X

### Accessories / Additional Parts

Accessories	Article number
Pad drive harpoon grip 28 cm	7510634
Scrubbing brush standard 28 cm	7510631
Scrubbing brush washed concrete 28 cm	7510632
Scrubbing brush abrasive 28 cm	7510633
Filling hose with universal water coupling	8502830
Additional Parts	Article number
Polyurethane traction wheel, brown	4122526 (17605-10)
Polyurethane wheel soft	4123154 (17608-40)
Polyurethane castor wheel 100mm	4122527 (17605-71)
External hour counter	4075260 (4991/105)

## **Description of Features**

**BMS: Battery Management System:** The battery charger which is integrated in the machine, prevents deep discharging of the battery and monitors the charging processs.

WD: Wheel Drive: The variable working speed (up to 4.5km/h) and reverse speed (up to 2.5km/h) guarantees ergonomic and effortless working and increases the performance compared to non-wheel drive models.

CSD: Cleaning Solution Dosing: With the patented CSD system, exactly the right amount of cleaning solution is dosed onto the floor depending on how fast the machine is going. The slower you go (e.g. around corners) the less is dosed. The result is no puddles around corners, a 30-50% saving in cleaning solution and significantly increased productivity of the machine.

**EBU:** Electrical Brush Unit: The brush unit can be lifted and lowered at the touch of a button. This allows fast and effortless brush changing - even for inexperienced users.



JohnsonDiversey Eschlikonerstrasse CH-9542 Muenchwilen Switzerland Ph. +41-71-969 2727 Fax. +41-71-969 2253 www.johnsondiversey.com

