



TASKI[®] swingo 760 B

Battery-powered automatic scrubber drier



Key Features

- Agility and high performance
- Excellent cleaning and drying result
- Durability and robustness
- Simplicity and easy maintenance

Perfectly combined agility and high performance

The TASKI swingo 760 B is very easy to handle and offers maximum agility for use in confined areas. The dual-axle system allows the machine to turn literally on the spot, which leads to excellent maneuverability in tightly congested areas. The 40 litre tank volume reduces the time-consuming tank filling stops during the cleaning operation.

Excellent cleaning and drying results

The machine's patented brush design follows the floor profile and delivers nearly even pressure allocation along the full working width, which leads to excellent soil removal. The patented V-shaped squeegee enables excellent water pick-up on the all floor types, even on structured and grouted / tiled floor. Special squeegee blades and a direct suction line allow pick-up of small debris (e.g. cigarette butts) without clogging. Due to the proven 3-castor wheel concept, adjustments of the squeegee are no longer necessary.

Durability and robustness

The use of high-tech glass fibre re-enforced non-corrosive material and long life components e.g. elastic Polypropylene tank material, enhance the machine's uptime, while reducing service and repair costs to a minimum. Splash water protection of all electrical elements also enhances safety and prolongs the lifetime of the machine.

Simple to use and easy maintenance

All components needing frequent maintenance are color-coded in yellow and can be removed easily without tools. The ergonomic handle suits all operators. All functions of the machine can be operated from the working position. The dashboard is self-explanatory and displays all relevant information. These features allow trouble-free operation and require minimum operator training.

TASKI swingo 760 B Specifications

Technical Data

Description		Description	
Theoretical performance	1290 m2/h	Dimensions (L x W x H)	116x47.5x119.5cm
		Turning circle	1.12 m
Working width	43 cm	Brush system	1 x 43 cm
Squeegee width	69 cm	Brush pressure	43 kg
Solution tank (nominal)	40	(with / without wheel drive)	+5 kg
Recovery tank (nominal)	401	Working speed (power)	3 km/h
Nominal consumption	900 W	Power cord length of	3 m
Rated voltage	24 V	integrated battery charger	
Battery capacity	50-70 Ah/C5	Sound level	58 dB(A)
Battery run time (nominal)	2 h	Electrical protection class	III
Machine weight ready for use	155 kg	Approvals	CE/CB Test cert.

TASKI swingo 760 B

Model	SKU Number
TASKI swingo 760 B Economy	7518540

Accessories/Additional Parts

Description	SKU Number
Pad drive harpoon grip 43 cm	7510829
Scrubbing brush standard 43cm	8504750
Scrubbing brush washed concrete 43cm	8504800
Scrubbing brush abrasive 43 cm	8504780
Filling hose with universal water coupling	8502830
Variety of polyester and contact pads	Please refer to local price list







TASKI[®] swingo 760 E

Cable powered automatic scrubber drier



Key Features

- Agility and high performance
- Excellent cleaning and drying result
- Durability and robustness
- Simplicity and easy maintenance

Perfectly combined agility and high performance

The TASKI swingo 760E is very easy to handle and offers maximum agility for use in confined areas. The dual-axle system allows the machine to turn literally on the spot, which leads to excellent maneuverability in tightly congested areas. The 40 litre tank volume reduces the time-consuming tank filling stops during the cleaning operation.

Excellent cleaning and drying results

The machine's patented brush design follows the floor profile and delivers nearly even pressure allocation along the full working width, which leads to excellent soil removal. The patented V-shaped squeegee enables excellent water pick-up on the all floor types, even on structured and grouted / tiled floor. Special squeegee blades and a direct suction line allow pick-up of small debris (e.g. cigarette butts) without clogging. Due to the proven 3-castor wheel concept, adjustments of the squeegee are no longer necessary.

Durability and robustness

The use of high-tech glass fibre re-enforced non-corrosive material and long life components e.g. elastic Polypropylene tank material, enhance the machine's uptime, while reducing service and repair costs to a minimum. Splash water protection of all electrical elements also enhances safety and prolongs the lifetime of the machine.

Simple to use and easy maintenance

All components needing frequent maintenance are color-coded in yellow and can be removed easily without tools. The ergonomic handle suits all operators. All functions of the machine can be operated from the working position. The dashboard is self-explanatory and displays all relevant information. These features allow trouble-free operation and require minimum operator training.

TASKI swingo 760 E Specifications

Technical Data

Description		Description	
Theoretical performance	1290 m²/h	Dimensions (L x W x H)	116x47.5x119.5cm
Working width	43 cm	Brush system	1 x 43 cm
Squeegee width	69 cm	Brush pressure	30 kg
Solution tank (nominal)	501	Working speed	3 km/h
Recovery tank (nominal)	501	Cable length	25 m
Nominal consumption	1500 W	Sound level	69 dB(A)
Rated voltage	120 V / 60 Hz; 230-240 V / 50 Hz	Protection class)	I
Machine weight ready for use	130 kg	Approvals	CE/CB Test cert.

TASKI swingo 760 E

Model	SKU Number
TASKI swingo 760 E	7518543 / 7518544

Accessories/Additional Parts

Description	SKU Number
Pad drive harpoon grip 43 cm	7510829
Scrubbing brush standard 43 cm	8504750
Scrubbing brush washed concrete 43 cm	8504800
Scrubbing brush abrasive 43 cm	8504780
Variety of polyester and contact pads	Please refer to price list

