



TASKI® swingo 855 B

TASKI swingo 855 B brings you:

- Agility and high performance
- Excellent cleaning & drying result
- Durability and robustness
- Simplicity and easy maintenance



Perfect combination of agility and high performance

The swingo 855 B is an agile machine which is easy to handle while offering increased productivity due to wide working width. The 50 cm brush unit allows very efficient cleaning, also close along walls and leads to great performance. The 40L tank volume and the patented CSD system radically increase performance and reduce the time consuming tank filling stops during the cleaning operation.

Excellent cleaning & drying results

The patented brush follows the floor profile and delivers nearly even pressure allocation along the full working width, which leads to excellent soil removal. The new and patented V-shaped squeegee enables excellent water pick-up on the floor. Due to the proven 3 wheel concept, adjustments of the squeegee are not necessary anymore.

Battery powered automatic scrubber drier for floor cleaning

Durability and robustness

The use of high tech material and long life components, enhance machine's uptime while reducing service & repair costs to a minimum.

Simple use and easy maintenance

All components which need frequent maintenance are colour coded in yellow and can be removed easily without tools. The dashboard is self explanatory and displays all relevant information. These features allow trouble-free operation with a minimum of operator training needed.

Technical Data

Theoretical performance (Power)	2250 m ² /h
Working width	50 cm
Squeegee width	69 cm
Solution tank (nominal)	40 L
Recovery tank (nominal)	40 L
Nominal consumption	900 W
Rated voltage	24 V
Battery capacity	50- 70 Ah/C5
Battery autonomy (nominal)	up to 2 h
Machine weight ready for use (Power)	160 kg
Dimensions (L x W x H)	1220x530x1195 mm
Turning circle	1.12 m
Brush system	1 x 50 cm
Brush pressure (with wheel drive)	43 kg
Working speed (Power)	4.5 km/h
Cable length of integrated battery charger	3.0 m
Sound level	58 dB(A)
Electrical protection class (BMS / non BMS)	Class I / III
Approvals	CE/CB Test cert./ ÖVE/cETL

TASKI swingo 855 B is available in the following versions

Model	Power	Power BMS
Wheel Drive (WD+CSD)	x	X
Battery Management System (BMS)		X

Accessories / Additional Parts

Accessories	Article number
Pad drive harpoon grip 50 cm	7510830
Scrubbing brush standard 50 cm	8504770
Scrubbing brush washed concrete 50 cm	8505120
Scrubbing brush abrasive 50 cm	8505130
Variety of polyester and contact pads	Please refer to local price list
Additional Parts	Article number
Polyurethane traction wheel, brown	4122526 (17605-10)
Set of 2 polyurethane traction wheels green (supergrip)	4122746 (17608-50)
Polyurethane castor wheel 100mm	4122527 (17605-71)
External hour counter	4075260 (4991/105)

Description of Features

BMS (Battery Management System): The battery charger which is integrated in the machine, prevents deep discharging of the battery and monitors the charging process.

WD (Wheel Drive): The variable working speed (up to 4.5 km/h) and reverse speed (up to 2.5 km/h) guarantees ergonomic and effortless working and increases the performance compared to non-wheel drive models.

CSD (Cleaning Solution Dosing): The CSD-system allows speed-dependent supply of cleaning solution. This means the amount of solution used per m2 is always constant - no matter how fast the machine goes.



JohnsonDiversey
Eschlikonerstrasse
CH-9542 Muenchwilten
Switzerland
Ph. +41-71-969 2727
Fax. +41-71-969 2253
www.johnsondiversey.com

