



The next generation of automatic scrubber driers for floor cleaning

TASKI swingo XP brings you:

- Greatly increased productivity
- Best cleaning results
- Immediately dry floors
- Reduced water and energy consumption



Greatly increased productivity

The new stand-on concept with sensor steering combines excellent manoeuvrability with speed for faster cleaning. A highly efficient water management system reduces the number of time consuming tank-filling stops.

Best cleaning results

The new scrubbing unit with micro-rotating brushes offers improved cleaning results while saving up to 50% of cleaning solution vs. conventional brush systems.

Immediately dry floors

The excellent drying result allows use of the machine at any time of the day, while reducing the potential risk of slip fall accidents caused by wet floors.

Reduced water and energy consumption

The highly efficient use of these natural resources makes the machine environmentally friendly and helps reduce costs.

Technical Data	
Theoretical performance	4500 m2/h
Working width	75 cm
Squeegee width	95 cm
Solution tank - bag system	105 I
Recovery tank	105 l
Rated voltage	24 V
Nominal consumption	1200 W
Battery capacity (max)	195 Ah/C5
Battery autonomy	3.5 h
Machine weight net	180 kg
Machine weight ready for use (w/o driver)	410 kg
Dimensions (L x W x H)	119 x 95 x 126 cm
Door pass through width (w/o squeegee)	85 cm
Brush system	2 units 45x15 cm
Micro-rotation speed of brushes	550 rpm
Brush pressure min - max	0.33 - 0.67 N/cm2
Cleaning speed	6 km/h
Sound level	65 dB(A)
Splash water protection	IPX3



TASKI swingo XP BMS

Model	Article number
TASKI swingo XP BMS Euro	7514505

Accessories / Additional Parts

Description	Article number
Scrubbing brush Nylon 450 mm	7514650
Pad drive harpoon grip 450 mm	7514648
TASKI contour contact pad 450 mm (pack of 4)	7514732
TASKI contour pad 450 mm White (pack of 10)	7514727
TASKI contour pad 450 mm Red (pack of 10)	7514728
TASKI contour pad 450 mm Blue (pack of 10)	7514729
TASKI contour pad 450 mm Brown (pack of 10)	7514730
TASKI contour pad 450 mm Black (pack of 10)	7514731
Filling hose with universal coupling	8502830

Description of Features

BMS - Battery Management System: The battery charger is integrated in the machine. A monitoring system prevents deep discharging of the battery and controls the charging process.

CSD - Cleaning Solution Dosing: With the patented CSD system exactly the right amount of cleaning solution is dosed onto the floor. The result is no puddles in curves and turns as well as a 30-50% saving in cleaning solution which leads to significantly increased productivity of the machine.



JohnsonDiversey
Eschlikonerstrasse
CH-9542 Muenchwilen
Switzerland
Ph. +41-71-969 2727
Fax. +41-71-969 2253
www.johnsondiversey.com

